


THA




10.25

PRELIMINARY



AGRICULTURE



Machine model	Telescopic handler	THA 10.25
	Maximum lifting capacity	10,000 lb
	Maximum lifting height	25' 3"
	Maximum reach	13' 9"
Engine	Model	FPT N45 Stage V
	Rated power	125 kW (170 hp) at 2,200 rpm
	Maximum torque	525 lb/ft at 1,500 rpm
	Displacement	4.5 l
	Cylinders	4 in line
	Engine type	Turbocharged direct injection diesel
	Cooling system	Water – intercooler
Transmission	Type	Hydrostatic
	Maximum pressure	510 bar
	Gearbox	Dropbox, 2 speeds forward-reverse
Axles and brakes	Type	Axles with planetary gearboxes
	Front axle	Steering
	Rear axle	Oscillating and steering
	Sideshift	-
	No. of driving wheels - steering wheels	4WD - 4WS
	Steering modes	Frontal/Concentric/Crab
	Service brake	Wet multi-disk on front and rear axle
	Parking brake	Hydraulic with negative action on front and rear axles
	Tyre sizes	460/70 R24
Performance	Max. travel speed	25 mph
	Turning radius (over tyres)	11' 8"
	Tractive effort	9,600 daN
Weights	Total unladen*	18,700 lb
Tank and system capacities	Diesel fuel	34 U.S. gal
	AdBlue	5.3 U.S. gal
	Hydraulic fluid	34 U.S. gal
	Engine oil	3 U.S. gal
	Cooling liquid	-
Hydraulic circuit for movements	Circuit type	Electronic load sensing
	Service pump	Variable displacement
	Max. hydraulic flow rate	34 U.S. gpm
	Max. boom head hydraulic flow rate	26 U.S. gpm
	Max. working pressure	350 bar
	Distributor for boom movements	Electro-proportional valve
	Movements control	1 joystick with integrated manoeuvre enable
Road type approval	167/2013: Mother Regulation	T1a
Standards met	2006/42/EC: EU Machinery Directive	
	2000/14/EC: Noise Directive	
	EN 1459-1: relating to standards on the safety requirements for variable-reach trucks	
	EN 280-1: standards relating to mobile elevating work platforms (if available)	
	2014/30/EU: EMC Directive	
	ROPS/level 2 FOPS: relating to the standards for protective structures	

The data given in this brochure are provided for information purposes and are subject to change without prior notice.

All images are purely guideline and might not give an exact representation of the product.

*the stated weight refers to the vehicle unladen with standard equipment and may vary depending on the chosen configuration.